


SEC:A-A



SEC:B-B

Ordering Information & Specifications

| PART NO.      | Wire Range | Insulation O.D. | Material        | Finish           | Qty/reel  |
|---------------|------------|-----------------|-----------------|------------------|-----------|
| C3030M-TPE    | AWG#20-#24 | 1.85mm(max)     | Phosphor Bronze | Tin-plated       | 15,000pcs |
| C3030M-HPE    | AWG#20-#24 | 1.85mm(max)     | Phosphor Bronze | Gold-flash       | 15,000pcs |
| C3030M-HPE-G1 | AWG#20-#24 | 1.85mm(max)     | Phosphor Bronze | Gold-plated 15u" | 15,000pcs |
| C3030M-HPE-G2 | AWG#20-#24 | 1.85mm(max)     | Phosphor Bronze | Gold-plated 30u" | 15,000pcs |

Note:E-Stamping before Tin-plated or Gold-plated

|      |             |                   |             |  |  |
|------|-------------|-------------------|-------------|--|--|
|      |             |                   |             | <b>JOINT TECH ELECTRONIC IND. CO., LTD.</b><br><b>JOY DAY INDUSTRIAL CO., LTD.</b> |  |
|      |             | UNIT              | SCALE       | SHEET  | TITLE:   |
|      |             | mm                |             | 1 of 1   | <b>3.00mm PITCH<br/>CRIMP TERMINAL-MALE,<br/>MICRO-FIT</b> |
|      |             | DRAWN BY          | APPROVED BY |  |  |
|      |             | 董正一               | 董正一         |  |  |
|      |             | 2001.02.01        | 2001.02.01  |  |  |
|      |             | GENERAL TOLERANCE |             |  |  |
| B2   | REVISE      | 2006.04.24        |             |  |  |
| B1   | REVISE      | 2006.01.19        | X. X±0.25   | ANGLE±   |  |
| B0   | NEW RELEASE | 2005.12.14        | X. XX±0.15  |  |  |
| REV. | DESCRIPTION | DATE              | X. XXX±0.05 |  |  |
|      |             |                   |             |  | DRAW NO. :   |
|      |             |                   |             |  | C3030M-XX  |
|      |             |                   |             |  | REV. B2  |