

质量见证一切
 科技创造无限

QUALITY WITNESS EVERYTHING, SCIENCE AND TECHNOLOGY TO CREATE UNLIMITED



Categories: Potentiometer, Multi-Turn Cermet trimmer Potentiometer

Model: 3296W



Description:

Cermet Trimmer Potentiometer 3296W		
Electrical Characteristics	Standard Resistance Range	10Ω~2MΩ
	Resistance Tolerance	±10% ±20%
	Terminal Resistance	≤1%R or 2Ω
	Insulation Resistance	R1≥ 1GΩ
	Rated Power (300V)	+70°C 0.5W; +125°C 0W
	Withstand Voltage	101.3kPa 600V 8.5kPa 360V
	Contact Resistance Variation (CRV)	≤3%R or 3Ω
	Effective Electrical Travel	30±2 cycles
Environment Characteristics	Temperature Range	-55°C~+125°C
	Temperature Coefficient	±250, ±100ppm/°C
	Collision (390m/S ² , 4000 times)	390m/s ² ΔR≤±1%R
	Vibration (10-500HZ, 0.75mm or 98m/ 6h)	ΔR≤±1%R, ΔUab/Uac≤±2%R
	Temperature Variation	ΔR≤±2%R, ΔUab/Uac≤±1%R
	Climate Category	ΔR≤± 3%R, R1≥100MΩ
	Electrical Endurance (70°C,0.5W,1000h)	ΔR≤± 3%R
	Mechanical Endurance (200 cycles)	ΔR≤± 3%R
Physical Characteristics	Steady Damp-Heat	ΔR≤± 3%R, R1≥100MΩ
	Total Mechanical Travel	30±2 cycles
	Starting Torque	≤36mN.m
	Clutch Torque	≤36mN.m

3296W Dimensions

