








































	Type no HT-	Die P/N	Specifications	Crimping cable size
	336M	3M	.288"/.268"/.305" 5.79/1.73/7.75mm	RG58, 59, 6, 62, 142
	336P1	3P1	.255"/.213"/.098"/.068"/.321" 6.48/5.41/2.49/ 1.73/8.15mm	RG58, 59, 62, 6
	336T1	3T1	.028"/.039"/.047"/.100"/.128" .151" 0.71/0.99/1.19/2.54 /3.25/3.84mm	RG174, 178, 179, 180, 187
	336V	3V	.043"/.100"/.151" .069"/.128"/.213" 1.09/1.75/2.54/3.25 /3.84/5.41mm	SMA, SMB, SMC, MCX
	336V1	3V1	.047"/.068"/.178"/.217"/.256" .330" 1.19/1.73/4.52/5.51 /6.50/8.38mm	RG59, 62, 6, 174, Fiber Optic
	336Y	3Y	.044"/.057"/.068"/.220"/.213" 1.12/1.45/1.73/5.59/5.41mm	RG58
	336Y1	3Y1	.218"/.069" 5.54/1.75mm	RG58(Oval Type)
	336Y2	3Y2	.042"/.240" 1.07/6.10mm	Pin terminal, insulated or non-insulated ferrules (Oval Type)
	236C	2C	AWG 20-18/16-14/12-10 DIN 0.5-1/1.5-2.5/4-6mm ²	Non-insulated terminal or open barrel terminal 
	236C2	2C2	AWG 20-18/16-14 DIN 0.5-1/1.5-2.5mm ²	Non-insulated terminal or open barrel terminal 
	236C3	2C3	AWG 24-30/18-22 DIN 0.25-0.05/1.0-0.5mm ²	D-Sub terminal 
	236C4	2C4	AWG 24-28/20-22 DIN 0.25-0.08/0.75-0.5mm ²	D-Sub terminal 
	236E	2E	AWG 22/20/18/16/14/12 DIN 0.5/0.75/1.0/1.5/2.5/4mm ²	Pin terminal insulated or non-insulated ferrules 
	236E1	2E1	AWG 10/8/6 DIN 6/10/16 mm ²	Pin terminal insulated or non-insulated ferrules 
	236E2	2E2	AWG 22/20/18/16/14/12/10/8/6 DIN 0.5/0.75/1.0/1.5/2.5/4 /6/10/16 mm ²	Pin terminal insulated or non-insulated ferrules 
	236E3	2E3	AWG 22/20/18/16/14/12/10 DIN 0.5/0.75/1.0/1.5/2.5/4/6 mm ²	Pin terminal insulated or non-insulated ferrules 
	236F	2F	AWG 22-18/16-14 DIN 0.5-1.0/1.5-2.5 mm ²	Insulated flag terminal 
	236F1	2F1	AWG 22-18/16-14 DIN 0.5-1.0/1.5-2.5 mm ²	Non insulated flag terminal 
	236H	2H	AWG 22-18/16-14/12-10 DIN 0.5-1.0/1.5-2.5/4-6 mm ²	Insulated terminal 
	236N	2N	AWG 20-18/16-14/12-10/8 DIN 1.5/2.5/6/10 mm ² JIS 1.25/2.0/5.5/8 mm ²	Non-insulated terminal 
	236R	2R	AWG 22-18/16-14/12-10 JIS 1.25/2.0/5.5 mm ²	Vinyl insulated w/o copper sleeve 
	236U	2U	AWG 14-22 DIN 2.5-0.5 mm ²	Non-insulated, open barrel & d-sub V.35 terminal 
	236W	2W	AWG 22-18/16-14/12-10 DIN 0.5-1.0/1.5-2.5/4-6 mm ²	Insulated terminal 
	301		AWG 22-18/16-14/12-10 DIN 0.5-1.0/1.5-2.5/4-6 mm ² HT-301 DIE is unchangeable	Insulated terminal 