


2.00


3.9



2.00

A

B



4.50

0.5

6.40

SPECIFICATIONS

Electrical

Current Rating: 2A AC, DC

Voltage Rating: 100V AC/ max.

Operating Temp.: -25°C ~ +85°C

Insulation Resistance: 1000MΩ / min.

Dielectric Withstanding Voltage: 800V AC/ min.

Contact Resistance: 20mΩ / max.

Material

Material: Nylon 66, UL94V-0

Poles	Dimension mm (in.)	
	A	B
2	2.0(0.079)	5.8(0.228)
3	4.0(0.157)	7.8(0.307)
4	6.0(0.236)	9.8(0.386)
5	8.0(0.315)	11.8(0.465)
6	10.0(0.394)	13.8(0.543)
7	12.0(0.472)	15.8(0.622)
8	14.0(0.551)	17.8(0.701)
9	16.0(0.630)	19.8(0.780)
10	18.0(0.709)	21.8(0.858)
11	20.0(0.787)	23.8(0.937)
12	22.0(0.886)	25.8(1.016)
13	24.0(0.945)	27.8(1.094)
14	26.0(1.024)	29.8(1.173)
15	28.0(1.102)	31.8(1.252)
16	30.0(1.181)	33.8(1.331)

所有材料為
"環保材料"

2006.7.10

RoHS

YY01CXX

DESCRIPTION(內容):
2.0mm Wire-to-Board Housing

DRAWN(製圖):
mini
CHECKED(確認):
Mandy

GENERAL TOLERANCE:
(公差)
XXX ± 0.2
XX ± 0.3

REV:	REV	DESCRIPTION	DATE
R2	R0		2006.01.18
UNIT:	R1	環保料	2006.07.10
mm	R2	變更環保字樣	2006.08.15
SIZE:	R3		
A4			
SHEET:			
1/1			

PREP NO:
料號:
DWG NO(圖號): 2000J-H

APPROVAL(核准):
Johnny

SCALE(比例):
Free

